

FEATURE	NWA50AX		NWA55AXE		NWA90AX	
	Simple mode	Advanced mode	Simple mode	Advanced mode	Simple mode	Advanced mode
Model						
SSID settings	Simple mode	Advanced mode	Simple mode	Advanced mode	Simple mode	Advanced mode
Name	•	•	•	•	•	•
WLAN Security						
Open	•	•	•	•	•	•
WPA2-PSK	•	•	•	•	•	•
WPA3-PSK		•		•		•
Enhanced-Open		•		•		•
DPPSK		!		!		!
MAC Authentication		!		!		•
WPA2-Enterprise		!		!		•
WPA3-Enterprise		!		!		•
Traffic Option						
Forwarding mode - Local bridge		•		•		•
Forwarding mode - NAT mode		!		!		!
Forwarding mode - Tunnel mode		!		!		!
Rate-limit		•		•		•
Advance settings						
VLAN ID		•		•		•
Band mode		•		•		•
Layer2 isolation (Guest network)		!		!		•
Intra-BSS traffic blocking		•		•		•
Band select		•		•		•
Assisted roaming		•		•		•
802.11r		•		•		•
U-APSD		•		•		•
Sign-in method						
Click-to-continue		!		!		•
Voucher		!		!		•
Sign-on with Nebula cloud server		!		!		•
Sign-on with MyRADIUS server		!		!		•
Sign-on with Facebook		!		!		•
Sign-on with Facebook WIFI		!		!		•
Wireless health						
Smart Mesh	•		•		•	
Wireless bridge			•			
Radio whole settings	•		•		•	

Note: SSID will be turned off while non-supported feature mark as "!" applied to NWA50AX, NWA55AXE or NWA90AX.